




MT



PRESSURE CAPSULE DETAILS




No. Description

1. Low Pressure Port (SS)*
2. Support Plate (SS)
3. Gasket (PTFE®)
4. Bottom Flange (SS)
5. Support Spring (SS)
6. Mounting Adaptor (SS)
7. Spring Support (SS)
8. Spring Locating Pin (SS)
9. Sealing Ring (PTFE®)
10. Support Ring (SS)
11. Transfer Pin (SS)
12. Top Flange (SS)
13. Diaphragm (Neoprene)
14. Clamping Screw (CS)
15. O-Ring (Viton)
16. High Pressure Port (SS)*
17. O-Ring (Viton)

Note : *wetted parts* are mentioned in italics.

*Pressure ports are brazed with flange

INSTALLATION DRAWING



RANGE SELECTION TABLE

Range Code	Range mbar ("Wc)	Differential* mbar ("Wc)	Maximum Working Pressure bar (psi)
		Approximate Maximum for "A1" microswitch	
U15	0.4 - 1.5 (0.16 - 0.6)	0.50 (0.20)	0.5 (7.25)
U25	0.5 - 2.5 (0.2 - 1.0)	0.80 (0.32)	0.5 (7.25)
U40	1.0 - 4.0 (0.4 - 1.6)	1.20 (0.48)	0.5 (7.25)

Note:

1. The minimum differential increases with the setpoint. The differential values mentioned in the above table are approximate maximum for FSR. The differential value will vary according to the pressure range selected and microswitch type. For actual values of differential please contact sales office.

2. When using 2SPDT switching arrangement, both microswitches may not actuate and/or deactuate at the same point. A small stage gap, normally upto +/- 5% FSR (depending on range code) may be observed. The On-Off differential (hysteresis) typically tends to be atleast double of those published for 1SPDT pressure switches.

If actuation and/or deactuation at same point is critical part of operation, then it can be achieved by using a separate DPDT relay. This relay will need a separate power supply for it's coil.

HOW TO ORDER INDUSTRIAL ULTRA LOW RANGE PRESSURE DIFFERENCE SWITCHES

Group 1	Group 2	Group 3	Group 4	Group 5	Group 6	Group 7	Group 8	
Non standard allocation	Model	Cable Entry Size	Switch Type	Range Code (values in mbar)	Microswitch Type	Pressure Port Material / Size	Diaphragm	
☐ A prefix "N" is used in the model code in case of any non standard options / accessories that are provided with the switches. Will be given by manufacturer, only after agreement of supply details with customer. The prefix is subject to change as per specific requirement.	MD = Industrial pressure switch with IP66 rated enclosure as per IS/IEC 60529 MT = Industrial pressure switch with IP66 rated enclosure as per IS/IEC 60529	1 = Al. enclosure ½" NPT threads *2 = Al. enclosure ¾" NPT threads 3 = Al. enclosure M20 X 1.5 threads 7 = SS enclosure, ½" NPT threads *8 = SS enclosure, ¾" NPT threads 9 = SS enclosure, M20 X 1.5 threads	*DF2 = pressure difference switch, fixed differential with scale in mbar *Df3 = pressure difference switch, fixed differential with scale in "Wc DA2 = pressure difference switch, adjustable differential with scale in DA3 = pressure difference switch, adjustable differential with scale in "Wc	U15 = (0.4 - 1.5) U25 = (0.5 - 2.5) U40 = (1.0 - 4.0)	A1 = General purpose microswitch, rated at 15 A; 250 VAC *A6 = Adjustable deadband *A7 = 2SPDT switching elements *A8 = General purpose microswitch *A9 = General purpose microswitch *B7 = 2SPDT Switching Elements *B9 = 2SPDT Switching Elements for adjustable differential	S1 = SS316 / ¼" BSP(F) S2 = SS316 / ¼" NPT(F)	0 = Neoprene 1 = TPTFE	
Approx. switch weight in Kgs								
Enclosure	MD	MT						
Aluminium	3.200	3.590						
SS	4.710	5.210						
		*Not available for MT model For dual cable entry contact Sales Office	*Available with A6, A7, A9 & B9 (in group 6) only		* Please refer to page nos. 290 & 291 for options and specifications of microswitches Please contact sales office for additional information			More options available, please contact sales office

eg. Industrial pressure switch with 1/2" NPT cable entry in aluminium housing as 1SPDT pressure switch, fixed differential with scale in mbar, having 0.16 to 0.60 "Wc pressure range, with 15Amp. microswitch, SS316 pressure housing with 1/4" BSP port size & neoprene diaphragm shall be specified by

Group 1	Group 2	Group 3	Group 4	Group 5	Group 6	Group 7	Group 8
☐	MD	1	DF2	U15	A1	S1	0

Please specify full model number to avoid ambiguity.

ULTRA LOW RANGE PRESSURE DIFFERENCE SWITCHES

MD/MT