

MICROSWITCH OPTIONS

Sr. No.	Switch Type	Description	Rating AC			Rating DC			Adjustable Differential
			Res.	Ind.	Voltage	Res.	Ind.	Voltage	
1	A1	General purpose	15	-	125/250/480	-	-	-	
2	A2	1SPDT Hermetically sealed Silver	2	-	115	5	2	28	
3	A3	Gold plated contacts	1	-	250	1	-	30	
4	A4	DPDT configuration	10	-	125/250	0.15/0.25	-	250	
5	A5	High DC rating	-	-	-	10/3	-	125/250	
6	A6	Adjustable deadband	15	-	115/250	1	-	24	✓
7	A7	2 SPDT	5	-	250	5	3	28	✓
8	A8	General purpose	5	-	125/250	5	3	28	
9	A9	General purpose	15	-	250	5	-	28	✓
10	B1	General purpose AC/ DC	15	-	125/250/480	0.25	-	250	
11	B2	2SPDT Hermetically sealed Silver	2	2	115	4	2	28	
12	B3	2SPDT Gold plated	1	-	125	-	-	-	
13	B4	Manual reset	15	-	125/250/480	0.25	-	250	
14	B5	1SPDT Hermetically sealed, gold plated contact	-	-	-	1	0.25	28	
15	B6	2SPDT Hermetically sealed, gold plated contact	-	-	-	1	0.25	28	
16	B7	2 SPDT	15	-	250	5	-	28	
17	B9	2 SPDT Adjustable	15	-	250	5	-	28	✓
18	C6	1SPDT Adjustable Differential	5	-	250	5	3	28	✓
19	C7	2SPDT Adjustable Differential	5	-	250	5	3	28	✓
20	C8	1 SPDT High DC Rating	15	-	250	5	-	250	
21	C9	1 SPDT High AC Rating	20	-	125/250/277	-	-	-	
22	D1	Orion Hermetically Sealed SPDT 15A	15	-	125/250/480	-	-	-	
23	D2	Orion Hermetically sealed Silver 1 SPDT	5	-	125/250	5	3	28	
24	D3	D3 Orion Hermetically sealed Gold plated 2 SPDT (Sub Miniature)	1	-	250	1	-	30	
25	D4	Orion Hermetically sealed DPDT config	10	-	125/250	0.15/0.25	-	250	
26	D5	Orion Hermetically sealed Silver 2 SPDT (Sub miniature)	5	-	125/250	5	3	28	

MICROSWITCH OPTIONS

Sr. No.	Switch Type	Description	Rating AC			Rating DC			Adjustable Differential
			Res.	Ind.	Voltage	Res.	Ind.	Voltage	
26	D5	Orion Hermetically sealed Silver 2 SPDT (Sub miniature)	5	-	125/250	5	3	28	
27	D6	Orion Hermetically sealed Gold plated 2 SPDT (Sub Sub Miniature)*	7	-	250	5	-	30	
28	D7	Orion Hermetically sealed Silver 2SPDT	7	-	250	7	4	28	
29	D8	Orion Hermetically sealed Gold plated 1 SPDT	1	-	125	1	0.5	30	
30	D9	Orion Hermetically sealed Gold Plated Contact 2 SPDT (Sub miniature)	1	-	125	1	0.5	30	
31	E1	Dual current Gold plated	0.1	-	250	-	5	250	
32	E2	General purpose AC/DC	15	-	250	6	-	30	
33	E3	2 SPDT – High DC Rating	15	-	250	5	-	250	
34	E4	Orion Gold plated 1 SPDT (Sub Sub Miniature)*	7	-	250	5	-	30	
35	E6	Orion Gold plated 2 SPDT (Sub Sub Miniature)*	7	-	250	5	-	30	
36	E5	Orion Hermetically sealed Gold plated SPDT (Sub Sub Miniature)*	7	-	250	5	-	30	
37	E7	Orion Hermetically sealed Silver 1 SPDT	15	-	125/250/480	0.25	-	250	
38	E8	Orion Hermetically sealed Silver 2 SPDT	10	-	125/250	5	5	30	